

## **Bolt Pack Specifications**

### **Bolts, Nuts, & Washers:**

#### Bolts:

- 304 Stainless Steel Finished Hex Head Bolts conforms to ASTM F593
- 316 Stainless Steel Finished Hex Head Bolts conforms to ASTM F594

#### Nuts:

- 304 Stainless Steel Finished Hex Nuts conforms to ASTM F593
- 316 Stainless Steel Finished Hex Nuts conforms to ASTM F594

#### Washers:

- 304 Stainless Steel Flat Washers are standard
- 316 Stainless Steel Flat Washers are standard

### **Red Rubber Gaskets:**

#### Colour:

- Red

#### Finish:

- Smooth

#### Physical Characteristics:

- Tensile: 500 PSI
- Elongation: 250%
- Hardness: 80 SHORE "A" +/- 5
- Temperature Range: -20°C to 80°C (-4°F to 176 °F)

#### Notes:

- An economical red sheet with a smooth finish used in low-pressure applications with no oil-resistant requirements. This rubber is also ideal for gaskets and other sheet applications where a recognizable red colour is required.

#### ISO/ASTM Designation:

- SBR

**Neoprene Gaskets:**

Colour:

- Black

Finish:

- Smooth

Physical Characteristics:

- Tensile: 620 PSI
- Elongation: 300%
- Hardness: 70 SHORE "A" +/- 5
- Temperature Range: -30°C to 82°C (-22°F to 180 °F)

Notes:

- An economical 70 Durometer black rubber gasket has been formulated to provide moderate oil and petroleum based solvent resistance. In addition, this gasket gives good weathering and ozone resistance for outdoor or unusual environmental conditions. This material is utilized in a broad range of industrial applications.

Commercial Grade ISO/ASTM Designation:

- CR

